



***Dishaa***<sup>®</sup>

BORING MACHINE

**CONTACT US**

**P.O. BOX: 80899, Dubai, UAE**

**Mob: +971 50 9696 477**

**Email: [sajith@dishaagroup.com](mailto:sajith@dishaagroup.com)**

**Website: [www.dishaagroup.com](http://www.dishaagroup.com)**

# Boring Machine

## TXK68 / TXK611

CNC Boring Machine



### Optional configuration

- pneumatic table 1° per turn
- CNC rotary table 1° per turn

SPECIFICATIONS	Units	TXK68	TXK611
Spindle bore	mm	155	155
Spindle taper	BT	BT50	BT50
Spindle speed	rpm	3000(servo drive)	1-3000(伺服驱动servo drive)
Table size (L*W)	mm	990*800 opt.1000*1000	1100*900 选配opt.1000*1000
Table longitudinal travel(Z axis)	mm	1200	1200
Table cross travel(X axis)	mm	650	1000
Spindle box travel(Y axis)	mm	700	900
Axial travel of spindle	mm		可选配伸缩主轴Optional telescopic spindle
Table feed speed	mm/min	1-2500	1-2500
Main motor power	kw	15	15
Positioning accuracy	mm	±0.025	±0.025
Repeat positioning accuracy	-	±0.015	±0.015
CNC control system	mm	KND/GSK	KND/GSK
Machine Weight	kg	6000	9000
Overall dimension	mm	4000*2200*2500	4000*3000*3000

# TX68 / TX611

Boring Machine



## Optional configuration

- Universal boring head
- Tailstock
- 3 Axis DRO
- Face milling cutter
- Boring bar

SPECIFICATIONS	Units	TX68	TX611
Spindle bore	mm	85	110
Spindle taper	-	MT5	MT6
Spindle speed	rpm	25-530(9steps)	25-450(9steps)
Table size (L*W)	mm	900*800	1100*900
Table longitudinal travel(Z axis)		1400(Without Tailstock)	1400(Without Tailstock)
Table cross travel(X axis)	mm	700	900
Spindle box travel(Y axis)	mm	700	900
Axial travel of spindle	mm	300	400
Table feed speed(steps)	mm/min	5-160(6 steps) servo	6-160(6 steps) servo
Table rapid traverse	mm/min	2000	2000
Spindle box lifting speed	mm/min	1-2500	1-2500
Main motor power	kw	4	5.5
Machine Weight	kg	5000	9000
Overall dimension	mm	2700*1600* 2100	3800*2200*2560