



***Dishaa***<sup>®</sup>

POWER PRESS

**CONTACT US**

**P.O. BOX: 80899, Dubai, UAE**

**Mob: +971 50 9696 477**

**Email: [sajith@dishaagroup.com](mailto:sajith@dishaagroup.com)**

**Website: [www.dishaagroup.com](http://www.dishaagroup.com)**

## Power Press Machine



### Features

- Steel plate welding machine, good rigidity, more stable accuracy.
- Crankshaft longitudinal, compact structure, beautiful appearance.
- Electric adjustment of the height of the mould, digital display control height.
- Rectangular block with a lengthened guide, bronze lining board, high guidance accuracy.
- Combined pneumatic friction clutch brake, joint stable, action sensitivity.
- Collapse type safety device, to ensure the safety of the whole machine.
- Slider is high, there is a lifting type balance cylinder, to achieve the balance of the slider bar.
- The slider can be moved with a small movement, emergency stop motion, more secure operation.
- The circuit uses double valve control, the action is nimble, accord with the safety standard of press.

### Application

- Suitable for blanking, punching, forming, bending, stretching and other cold stamping process to achieve.
- Widely used in electrical appliances, vehicles, tractors, mining machinery, hardware tools, machinery manufacturing and other industrial areas.

Specification	Units	JB23-16	JB23-63	JB23-80	JB23-100
Nominal pressure	KN	160	630	800	1000
Nominal force stroke	mm	2	4	5	5
Slider stroke	mm	50	80	100	100
Number of slider stroke	/min	140	50	50	40
Maximum die set height	mm	170	250	300	300
Die set height adjustment	mm	30	50	60	80
Distance from slider center to frame	mm	160	250	260	310
Worktable dimension	mm	320x460	420x650	470x750	570x860
Thickness of the worktable panel	mm	45	70	80	90
Size of the handle hole (diameter x depth)	mm	cp40x60	cp50x70	cp60x80	cp60x80
Vertical columns distance	mm	240	320	300	420
Main motor	Model	Y90L-4	Y132S-4	Y132S-4	Y132M-4
	Power	KW	1.5	5.5	5.5
Maximum tilting angle of body	°	25	25	20	20
Overall dimension (L x W x H)	mm	1130X830X1890	1740X1100X256	1765X1265X2560	1940X1490X2850
Weight	Kg	1090	3800	5015	6120