



Dishaa[®]

MAGNETIC DRILLING MACHINE

CONTACT US

P.O. BOX: 80899, Dubai, UAE

Mob: +971 50 9696 477

Email: sajith@dishaagroup.com

Website: www.dishaagroup.com

Bench Drilling Machine



PRODUCT DESCRIPTION:

Light and flexible, it can be used not only on machine processing, repairing but also DIY repairing and daily use.

STANDARD ACCESSORIES:

- Drill chuck
- Taper sleeve (only MT3 spindle)
- Arbor(only taper hole spindle)
- Drift(only taper hole spindle)
- Wrench

Technical Parameters

Model	DBD4113	DBD4125	DBD4132
Max. Drilling capacity(mm)	13	25	31.5
Diameter of column(mm)	70	85	85
Spindle travel(mm)	85	110	110
Distance spindle axis to generating line (mm)	180	200	200
Max distance spindle nose to worktable(mm)	390	480	480
Max. Distance spindle nose to base(mm)	570	670	670
Spindle taper(mm)	B16	Mt3	Mt3
Spindle speeds range(r/min)	450-2650	200-2280	150-2270
Spindle speeds series(r/min)	4	9	12
Dimension of worktable surface(mm)	240X240 or Φ300(Optional)	280×280 or Φ360(Optional)	280×280 or Φ360 (Optional)
Dimension of base(mm)	445x270	566x356	566x356
Overall height(mm)	960	1110	1110
Motor(W)	370	750	750
G.W/N.W(kg)	68/65	105/98	105/98
Packing size(cm)	91x51.5x27	108x77x34	108x77x34